

PG-S1



Dual Constellation, Dual Frequency Geodetic Antenna



- Featuring Topcon's High-performance Fence Antenna™ Technology
- Dual Constellation, Dual Frequency Geodetic Antenna
- L-Band Compatible
- Precision Tuned and Micro-centered Design
- Rugged Enclosure with High Shock and Vibration Tolerance

PG-S1 Dual Frequency, Dual Constellation Antenna



PG-S1 Dual Frequency, Dual Constellation Geodetic Antenna

The PG-S1 is a newly designed Topcon geodetic antenna built around patented Topcon Fence Antenna™ Technology. This high precision micro-centered antenna with integrated ground plane provides excellent tracking sensitivity and multipath rejection for all surveying and construction applications. The PG-S1 antenna supports L1/L2 frequencies from GPS and GLONASS satellite constellations, as well as L-Band frequencies. The PG-S1 can be paired with any Topcon modular or handheld GNSS receiver to provide a high performance dual-frequency RTK system.

The PG-S1 antenna system offers IP67 dust and water resistance as well as superior level of vibration and shock tolerance (IEC 60068-2). With its compact and ultra-rugged design, the PG-S1 is the most robust geodetic antenna in the market today.

Topcon TotalCare

This online resource comes with real live people ready to help. Get expert training from Topcon University's large collection of online materials, and expert help directly from Topcon Technical Support.

Access software and firmware updates, current publications, and guidance from the experts at Topcon all right from your computer or mobile device.

Please visit the TotalCare website to learn more.
topcontotalcare.com



7400 National Drive • Livermore • CA 94550
(925) 245-8300

Specifications subject to change without notice. ©2012 Topcon Corporation
All rights reserved. P/N: 7010-2091 Rev. B TF Printed in U.S.A. 9/12

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

SPECIFICATIONS

Operating Frequency Range

L1 GPS/GLONASS	1586.5 ± 25MHz
L2 GPS/GLONASS	1236 ± 20 MHz
L-Band	1535 ± 10 MHz

Out of Band Rejection

L1	± 100 MHz -30 dBc (typical)
L2	± 200 MHz -60 dBc (typical)

Gain, Noise Figure and VSWR

LNA Gain	33 dB (typical)
Gain at Zenith (90°)	GPS L1 5.5 dBic (min) GPS L2 5.5 dBic (min) GLONASS L1 4.5 dBic (min) GLONASS L2 4.5 dBic (min) L-Band 3 dBic (min)
Noise Figure	1.5 dB (typical)
VSWR	≤ 2.0:1
Nominal Impedance	50 Ohms

Connector and Mounting

Antenna Connector	TNC
Mount	5/8-11 UNC-2B thread

Physical Characteristics

Dimension (W x H x L)	141.6 x 141.6 mm x 54.2 mm
Diameter with Ground Plane	200 mm
Weight without ground plane	430 g
Weight with ground plane	615 g
Centering	< 1 mm, micro-centered

Power

Input Voltage Range	3-18 VDC. Reverse Polarity Protected
Power Consumption	55 mA (typical)

Environmental

Enclosure	Aluminum with Plastic Radome
Operating Temperature	-50°C to 85°C
Storage Temperature	-55°C to 85°C
Waterproof & Dust Rating	IP67
Random Vibration	IEC 60068-2-34, Test Fd
Sinusoidal Vibration	IEC 60068-2-6, Test Fc
Shock	IEC 60068-2-29 Test Ea
Bump	IEC 60068-2-29 Test Eb
Drop	2m pole drop to concrete

Your local Authorized Topcon dealer is: