

# PL-S1



## Dual Frequency, Dual Constellation Antenna



- Featuring Topcon's High-performance Fence Antenna™ Technology
- Dual Frequency, Dual Constellation GNSS Antenna
- L-Band Compatible
- Rugged Enclosure with High Shock and Vibration Tolerance

# PL-S1 Dual Frequency, Dual Constellation Antenna



## PL-S1 Dual Frequency, Dual Constellation Antenna

The PL-S1 is a newly designed dual-frequency and dual-constellation GNSS antenna offered at an affordable price. When accuracy requirements are flexible, this antenna is the best choice to provide maximum return on your investment. Like the geodetic-grade PG-S1 antenna, the new PL-S1 uses an integrated ground plane and Fence Antenna™ Technology for advanced multipath rejection and improved tracking sensitivity. For applications where Topcon's high-performance micro-centered antennas are not necessary, the PL-S1 delivers excellent signal tracking and mid-grade performance at an attractive price.

The PL-S1 antenna supports L1/L2 frequencies from GPS and GLONASS satellite constellations, as well as L-Band frequencies. The PL-S1 is designed to accompany all Topcon modular and handheld GNSS receivers when using Topcon's Spectrum RTK™ Technology.

## Topcon TotalCare

This online resource comes with real live people ready to help. Get expert training from Topcon University's large collection of online materials, and expert help directly from Topcon Technical Support.

Access software and firmware updates, current publications, and guidance from the experts at Topcon all right from your computer or mobile device.

Please visit the TotalCare website to learn more.  
[topcontotalcare.com](http://topcontotalcare.com)



7400 National Drive • Livermore • CA 94550  
(925) 245-8300

Specifications subject to change without notice. ©2012 Topcon Corporation  
All rights reserved. P/N: 7010-2092 Rev. B TF Printed in U.S.A. 9/12

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

## SPECIFICATIONS

### Operating Frequency Range

L1 GPS/GLONASS	1586.5 ± 25MHz
L2 GPS/GLONASS	1236 ± 20 MHz
L-Band	1535 ± 10 MHz

### Out of Band Rejection

L1	± 100 MHz -30 dBc (typical)
L2	± 200 MHz -60 dBc (typical)

### Gain, Noise Figure and VSWR

LNA Gain	33 dB (typical)
Gain at Zenith (90°)	GPS L1 4.5 dBic (min) GPS L2 3.5 dBic (min) GLONASS L1 3.5 dBic (min) GLONASS L2 2.5 dBic (min) L-Band 1 dBic (min)
Noise Figure	1.5 dB (typical)
VSWR	≤ 2.0:1
Nominal Impedance	50 Ohms

### Connector and Mounting

Antenna Connector	TNC
Mount	5/8-11 UNC-2B thread

### Physical Characteristics

Dimension (W x H x L)	141.6 x 141.6 mm x 54.2 mm
Diameter with Ground Plane	200 mm
Weight without ground plane	430 g
Weight with ground plane	615 g
Centering	< 1 cm

### Power

Input Voltage Range	3-18 VDC. Reverse Polarity Protected
Power Consumption	55 mA (typical)

### Environmental

Enclosure	Aluminum with Plastic Radome
Operating Temperature	-50°C to 85°C
Storage Temperature	-55°C to 85°C
Waterproof & Dust Rating	IP67
Random Vibration	IEC 60068-2-34, Test Fd
Sinusoidal Vibration	IEC 60068-2-6, Test Fc
Shock	IEC 60068-2-29 Test Ea
Bump	IEC 60068-2-29 Test Eb
Mechanical Drop	2m pole drop to concrete

Your local Authorized Topcon dealer is: